

Rack Sentry Temperature Sensor

PRODUCT OVERVIEW

The SensiNet Rack Sentry is a wireless temperature monitoring device and component of the SensiNet wireless sensor network. It reports highly accurate, real-time ambient level temperature measurements without wires and is FCC and CE-approved for license free operation worldwide.

The Rack Sentry utilizes a solid state sensor in a unique configuration for ultimate installation flexibility. Individual sensors are "daisy chained" using standard CAT5 patch cables. Up to three sensors are supported as standard and these sensors can be added and or reconfigured in the field. The system simply recognizes the attached sensors and reports temperature with virtually no user configuration.

Smart Sensor Benefits

Simple - Install and turn on...the system does the rest. Over the air configuration through standard web browsers eliminates complicated software. Sensors can even receive firmware updates over the network.

Robust - Rugged electronics combined with extensive self diagnostics provide a rock solid measurement system which continually monitors and reports system health such as battery voltage and connection status

Accurate - Self calibration and auto zero eliminates errors due to drift.

SensiNet Network Benefits

Reliable - Mesh networking provides multiple acknowledged and error checked communication paths ensuring the message always gets through while spread spectrum, frequency hopping radio technology eliminates interference effects. The network is also self healing and able to recover from interruptions by seeking alternate paths.

Flexible - Move, add or eliminate sensors and the network reconfigures itself automatically.

Universal - Multiple protocols including Modbus, OPC, SNMP, ODBC, and Web Services ensure system compatibility or operate the system as a stand alone data logging system with local or web based logging.

Scalable - The same network can start with a single point and grow to thousands without replacing any components or performance degradation.



SPECIFICATIONS

Radio Specifications	
Radio	IEEE 802.15.4 compliant, 2.4 GHz DFSS
Regulatory	FCC Part 15 and CE Approval
Antenna	Internal antenna
Output power	15 dBm
Range	<ul style="list-style-type: none"> • Up to 700 ft/212m range (outdoor, line of sight) • Up to 230 ft/70m range (typical indoor conditions)
Operating temperature	-10° C to 50° C
Operating humidity	Up to 100% non-condensing
Batteries	• "C" size 3.6 lithium thionyl chloride battery
Battery life	3 years at 2 minute reporting intervals
Update interval	User selectable 10 sec to 60 minutes
Dimensions	3.5" x 5.25" x 1.5"
Packaging	ABS Box - IP30 rated
Mounting	• Surface mount bracket included
Temperature Specifications	
Temperature range / accuracy	(-)40 to 125 C / +/-0.5 C