



SB110-NTC

Wireless Temperature Sensor (NTC)

The SB110-NTC is a battery powered sensor which can measure temperature using a Thermistor and send it over wireless a wireless link. Its integrated radio provides seamless wireless connectivity and an efficient power management algorithm enables long battery life. Up to three Thermistors can be “daisy chained” for multipoint applications such as server rack temperature monitoring.

When flexibility is essential, or in locations where running cables is inconvenient or not cost-effective, this wireless sensor is then your ideal solution. Based on our industry leading mesh networking protocol, the SB110 family delivers reliable performance even in harsh environments.

The integrated Thermistor sensor provides quick and reliable measurement at lower price compared to its pt100 compatriots. The measurement range is limited to -40°C to 125°C but is ideal for ambient temperature measurement applications like refrigeration, datacenter, and environmental conditions. SB110-NTC will automatically sample, log and transmit these readings in fully user-configurable intervals. Bi-directional communication is also supported, allowing the adapter to be wirelessly configured or calibrated. Configurable Set-points allow for a very flexible monitoring of temperature and humidity conditions for predictive maintenance applications.



Features and Benefits

- Thermistor sensor allows for quick reaction to temperature changes at lower measurement accuracy.
- Nodes can be line powered or run on batteries, with a battery life of multiple years
- Self-forming, self-healing mesh network topology for maximum resilience and ease of deployment
- Up to 90% installation and commissioning cost savings over traditional cable-based solutions
- Time synchronization of all nodes assures accurate time stamping of individual measurements
- Autonomous data logging and reporting, triggers, battery condition monitoring, over-the-air configuration and many other capabilities are given

Ideal for Monitoring Temperature in:

- Server Racks
- Cold Chains / Truck trailer
- Refrigerators & Freezer
- Healthcare Equipments
- Hospitals
- Museums
- School Food Service Equipments
- Laboratories, Blood & Tissue Bank
- Pharmaceutical

SB110-NTC is available with a choice of enclosure options, antenna types to suit most applications.



Antenna type ¹	External	External	
Antenna connector	Reverse-SMA	Reverse-SMA	Hirose U.FL
Enclosure rating	IP65	IP54	OEM module
Dimensions ²	98 x 64 x 38 mm (3.9 x 2.5 x 1.5")	98 x 64 x 38 mm (3.9 x 2.5 x 1.5")	72 x 53 x 35 mm (2.8 x 2.1 x 1.4")
Weight ³	160 grams (5.6 oz)	160 grams (5.6 oz)	35 grams (1.2 oz)
Operating temperature range	-20°C to +65°C ⁴ (-4 to 149 °F)	-20°C to +65°C ⁴ (-4 to 149 °F)	-40°C to +85°C (-4 to 149 °F)
Order code	SB110-NTC-E65	SB110-NTC-E54	SB110-NTC-O

¹ Internal antenna available on request

² Excluding antenna

³ Weight specifications of IP54 and IP65 include weight of batteries. Subtract 40 grams (1.4 oz) for weight of the product when externally powered

⁴ -40°C to +85°C available on request

Specifications

Wireless		General	
Radio type	IEEE 802.15.4 compliant	Sample rate (max.)	1 kHz
Frequency band	2.4 GHz	Scan cycle (typical)	10 s - 1 day
Standby current	20 µA	Scan cycle (min.)	100 ms
Active measurement current	12 mA	Sensor interface	Multi sensor interface, up to 3 sensors
Transmit current	55 mA	Sensor temperature range	-55 °C - +125 °C (-67 °F to +257 °F)
Receive current	50 mA	Resolution	0.5 °C
Node-to-node hops (max.)	3 ⁵	Accuracy	±0.5 °C, from -10 °C to +85 °C (17 to 185 °F)
Line of sight range (max.)	250 m (820') node-to-node ⁶	Battery lifetime ⁷ @ 3000 mAh	<ul style="list-style-type: none"> 15 min heartbeat - up to 7 years (Leaf), 3 years (Router) 5 min heartbeat - up to 5 years (Leaf), 18 months (Router)
In-building range (typical)	70 m (230') node-to-node	Power source	2 x AA batteries (3,000 mAh)
Receiver sensitivity	-92 dBm	Data log buffer	98 readings
Output power (max.)	2 dBm	Terminal cross-section	0.5 mm ² - 1.5 mm ²
Output power (typical)	0 dBm	EMC noise immunity	According to DIN-EN300328, DIN-EN50371
		EMC compatibility	According to DIN-EN60950
		Certifications	R/TTE, DIN-EN301489-1, DIN-EN301489-1, CE authorized for use in Europe

⁵ Extendable to up to 5 hops

⁶ Extendable to up to 2 km (6,500')

⁷ Longer battery life on request

Specifications are subject to change without notice.



12 Old Powerhouse Rd
Falmouth, ME 04105
888.928.4362
info@WirelessSensors.com
www.WirelessSensors.com